



For Good Measure!

THERMAL TRANSFER LABEL PRINTER

RP-4000H



Printing	Resolution	203dpi
	Printing Method	Direct Thermal
	Printing Speed	127mm/s(5inch/s)-150mm's Optional
	Max Printing Width	104mm
	Max Printing Length(Lable)	300mm
	Interface	USB
	Print Head (Abrasive Resistance)	150km
	Commands	TSC
Media	Max Media Roll OD	130mm
	Max Media Roll ID	24mm
	Media Paper Type	Continuous Paper,Lable Paper
	Media Width	Max 120mm.Min26.7mm
	Media Gap	Max.100mm
	Lable Length	20mm-300mm
	Accessories	Power Adapter,Power Cord,USB Cable,CD, Manual
		External Rear Bracket(Optional)
Software	Editing Software	Nicelabel SE
Character Font	Driver	XP,Win7,Win8,Win10
	Character Set	Gb18030
	Print Font	ASCII Font A:12*24
		ASCIIFontB:9*24
Barcode Type	ID Code	Code 39,Code93,Code128,ITF,ITF14,Subsets A,B,C,Codabar, EAN-8,EAN-13,EAN-14,EAN-128,UPC-A,UPC-E, EAM and UPC
		2 digits,add-on,MSI,MSIC,PLESSEY,CPOST
	2D Code	QR Code
	Graphics Processing	Support BMP/PCX/BAS
Picture Format	Temperature	Working:0-50 °C, Storage:-20~70 °C
	Humidity	Working:20%~85% ; Storage - 5%~95%
Power Supply		DC24V/2.5A
RAM/Flash		8MB/4MB
Dimension		217*182*172mm
Printer Weight		1.4kg