



For Good Measure!

LCD DIGITAL INDICATOR

THE T2200P PRINT



DESCRIPTION

Meet the T2200P Indicator: a compact, ABS plastic marvel offering surface or pole mounting flexibility. Its 6-digit 24mm LCD display with a white LED backlight ensures clear visibility, while the built-in thermal printer supports both label and receipt printing. Checkweighing, parts counting, and percentage weighing capabilities, delivers precision with a maximum of 7,500e divisions. RS232 communication port for PC connectivity and a rechargeable battery with a 35-hour lifespan, this indicator combines efficiency and technical excellence for streamlined weighing and printing.

FEATURES:

- Compact Design, constructed out of ABS Plastic
- Surface or pole mount
- Clear LCD display with White LED back light
- Built in Thermal Printer
- RS232 communication port for PC connection
- Checkweighing, Parts counting and percentage weighing for production.

SPECIFICATIONS:

- Max Divisions: 7,500e;30 000d
- Display: 6 digit 24mm LCD Display with White LED back light
- Housing : ABS Plastic
- Printer: Max Paper width 55mm, Max Printing Width 48mm.
- Printer Type: Label and Receipt
- Loadcell Excitation: 5VDC
- Minimum Input impedance: 43ohm
- Maximum Input impedance: 1600ohm
- Interface: RS232 Output as standard
- Power: Input AC100-240V, Output DC 12V/2500mA 6V/4Ah rechargeable battery
- Battery Life: 35 hours

DIMENSIONS

